imageRUNNER™ 5000i

Saddle Finisher-F2 | Puncher Unit-B1** | Finisher-F1 | imageRUNNER 5000i | Paper Deck-G1

imageRUNNER 5000i Specifications

Type:	Digital, Multifunction Imaging System
Imaging System:	Laser Dry Electrostatic Transfer
Developing System:	Dry Monocomponent Toner Projection
Image Server Memory:	Standard 192MB RAM + 5.1GB HDD (Max. Capacity: Approximately 4,000 Originals)
First-copy Time:	3.8 Seconds from Platen Glass 5.1 Seconds from ADF
Warm-up Time:	5 Minutes or Less
Acceptable Originals:	Sheets, Books, 3-dimensional Items (Up to 4.4 lb.)
Max. Original Size:	11" x 17" (Ledger)
Max. Copy Size:	11" x 17" (Ledger)
Min. Copy Size:	4-1/8" x 5-7/8"
Max. Mail Boxes Supported:	100
Max. Copy Reservation:	5 Jobs
Copy/Scanning Resolution:	600 dpi x 600 dpi
Printing Resolution:	600 dpi x 600 dpi 2400 dpi x 600 dpi Interpolated
Halftone:	256 gradations of gray
Copy Speed:	50 cpm (Letter) 39 cpm (Letter-R) 36 cpm (Legal) 30 cpm (Ledger)
Duplexing:	Standard Automatic Trayless Duplexing
Magnification Reduction/ Enlargement:	25% to 400% in 1% Increments
Paper Supply	
Standard:	Dual Front-loading Trays (1,500 Sheets Each) Dual Front-loading Cassettes (550 Sheets Each) 50-sheet Stack Bypass
Optional:	3,500-sheet Paper Deck (Total: 7,650 Sheets)
Multiple Copies:	1 to 999
Paper Weights:	17 to 24 lb. Bond (550-sheet Cassettes) 17 to 110 lb. Index (Manual Bypass, 1,500-sheet Drawers and 3,500-sheet Optional Paper Deck-G1)
Dimensions (H x W x D):	44-3/4" x 25-3/8" x 29-1/4" (1,136mm x 643mm x 743mm)
Weight:	462 lb. (210kg)

Supplies

Drum:	Amorphous Silicon – Estimated Yield: 3,000,000 Impressions
Maximum Duty Cycle:	200,000 Impressions per Month
Toner:	Magnetic Negative Toner – Estimated Yield: 33,000 Images (at 6% Coverage)

Communication Interface

Topology:	Ethernet
Speed:	10/100 Mbps Ethernet
Protocols Supported:	TCP/IP, IPX/SPX™, EtherTalk
Networked Interface Connections:	10/100Base-T (RJ-45)

Sending Functions

Sending Methods:	E-mail, I-fax, Database (Salutation), File Server (IPX, FTP, SMB)
Address Book Capacity:	Maximum 1,800
File Format: (E-mail, Database File Server)	Single Page TIFF, Multipage TIFF, PDF
Sending Sizes:	Statement to Ledger
Scanline Density:	200 x 100 dpi, 200 x 200 dpi 200 x 400 dpi, 400 x 400 dpi

ACCESSORIES

Automatic Document Feeder (Standard)

Acceptable Originals:	Statement to Ledger
Capacity:	100 Sheets (Letter/20 lb.)
Max. Paper Weight:	Up to 32 lb. Bond (Letter)

Network Multi-PDL Printer Kit-A2 (Standard)

Processor:	Canon Custom Processor—Shared
RAM:	192MB (Std./Max.)—Shared
Hard Disk:	5.1GB
PDL Support:	PCL® 5e, PCL® 6, PostScript® 3 Emulation
Internal Fonts:	136 PostScript Fonts 117 Adobe® Type Fonts 19 TrueType® Fonts 80 PCL Roman Fonts 32 PCL Bar-code Fonts
Interface Connections:	RJ-45 (10/100Base-T) IEEE 1284 (Compatibility: Nibble, Byte and ECP Mode) Token Ring (Optional Card)
Protocol Stacks:	IPX/SPX: 802.2, 802.3, Ethernet II, 802.2 SNAP TCP/IP: SENS for Tornado from WindRiver AppleTalk®: 802.2 SNAP and AppleTalk Phase II Only
Network OS:	Novell® NetWare® v.3.2, 4.1, 4.11, 4.2, 5 (IPX/SPX) Windows® 95/98 (TCP/IP) Windows NT® 4.0 (TCP/IP) Windows® 2000 (TCP/IP) Solaris™ 1.x, 2.5 or Later (TCP/IP) Apple® System 7.5 or Higher (DDP)

Finisher-F1 (Optional)

Number of Trays:	2 Trays
Tray Capacity	
Top Tray:	1,000 Sheets (Letter) 500 Sheets (Ledger) Offset Stacking: Max. 30 Sets (All Sizes)
Lower Tray:	1,000 Sheets (Letter) 500 Sheets (Ledger) Offset Stacking: Max. 30 Sets (All Sizes)
Staple Position:	1- Top Corner 2- Side Margin
Max. Stapling Capacity:	50 Sheets (Letter/Statement) 30 Sheets (Letter-R/Legal/Ledger)
Power Source:	Directly From Main Unit
Dimensions (H x W x D):	41-3/8" x 26-3/8" x 24-1/4" (1,052mm x 669mm x 614mm)
Weight:	70.5 lb. (32kg)

Saddle Finisher-F2 (Optional)

Number of Trays:	2 Trays
Tray Capacity	
Top Tray:	1,000 Sheets (Letter) 500 Sheets (Ledger) Offset Stacking: Max. 30 Sets (w/Staple) (All sizes)
Lower Tray:	1,000 Sheets (Letter) 500 Sheets (Ledger) Offset Stacking: Max. 30 Sets (w/Staple) (All Sizes)
Saddle-stitch Tray:	300 Sheets
Staple Position:	1- Top Corner 2- Side Margin
Max. Stapling Capacity:	50 Sheets (Letter/Statement) 30 Sheets (Letter-R/Legal/Ledger)
Saddle-stitch Tray	
Stapling Capacity:	15 Sheets
Folding:	V-folding Standard
Power Source:	Directly From Main Unit
Dimensions (H x W x D):	41-3/8" x 26-3/8" x 24-1/4" (1,052mm x 669mm x 614mm)
Weight:	114 lb. (52kg)

Puncher Unit-B1** (Optional)

Max. Paper Weight:	Up to 110 lb. Index
Punch Types:	2-hole/3-hole (Auto Change) 3-hole (Letter/Ledger) 2-hole (Legal/Letter-R)
Punch Dust Stock:	Approximately 3,000 Sheets
Power Source:	Directly From Main Unit
Dimensions (H x W x D):	34-7/8" x 3" x 24-1/4" (886mm x 75.5mm x 614mm)
Weight:	11.9 lb. (5.4kg)

Paper Deck-G1

Paper Capacity:	3,500 Sheets
Paper Size:	Letter
Paper Weight:	17 lb. Bond to 110 lb. Index
Power Source:	Directly From Main Unit
Dimensions (H x W x D):	20-1/2" x 12-3/4" x 33" (519mm x 323mm x 583mm)
Weight:	90.3 lb. (41kg)

* Check with your local Canon-authorized Dealer for availability.

** Puncher Unit-B1 can only be used with the Finisher-F1 and Saddle Finisher-F2.

Canon KNOW HOW™

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. The ENERGY STAR name is a registered trademark of the U.S. Environmental Protection Agency. HP, PCL and OpenView are registered trademarks of Hewlett-Packard Company. Adobe and PostScript are registered trademarks of Adobe Systems Incorporated. Microsoft, Windows and Windows NT are registered trademarks of Microsoft Corporation in the United States and/or other countries. TrueType, AppleTalk and Apple are registered trademarks of Apple Computer, Inc. Novell and NetWare are registered trademarks, and IPX/SPX is a trademark of Novell, Inc. Solaris is a trademark of Sun Microsystems, Inc. eCopy and Desktop are trademarks of eCopy, Inc. Tivoli and NetView are registered trademarks of Tivoli Systems Inc. in the United States, other countries, or both. Patrol is a registered trademark of BMC Software, Inc. Canon and NetSpot are registered trademarks, and IMAGERUNNER, Canon Know How and the GENUINE logo are trademarks of Canon Inc. IMAGEANYWARE is a service mark, and Universal Send and Remote UI are trademarks of Canon U.S.A., Inc. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.

Specifications subject to change without notice.

0024W137

1001-iR5000i-100M

1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Plaza
Lake Success, NY 11042

PRINTED ON RECYCLED PAPER IN THE U.S.A.